

FEEL THE DIFFERENCE

ZVA SLIMLINE 2 + ZVA SLIMLINE 2 GR



ELAFLEX




HOW DOES A PERFECT NOZZLE LOOK?

The ZVA from ELAFLEX. During the last decades developments have been made to the renowned ZVA Slimline and ZVA 200 GR nozzle. New requirements such as a light lever action, cleaner fuelling and improved closing for 'to the penny dispensing' involved a completely new nozzle construction. The ZVA Slimline 2 generation.

Engaging with our customers we have stayed true to our philosophy of ergonomic design, interchangeable with existing nozzle booths, easy repair and service maintenance in the field using existing parts and tools.

The ZVA Slimline 2 generation is a detailed improvement package which can be felt and experienced during refuelling.



ZVA Slimline 2 :
Neutron / X-Ray image

DOUBLE VISION.

ZVA SLIMLINE 2

- Sets new standards for diesel and gasoline.
Also suitable for biodiesel and mixtures with biofuels such as ethanol.
- Replaces the ZVA Slimline from autumn 2008.
- Working pressure 0,5 up to 3,5 bar.
Flow rate up to 70 l/min
(depending on various pressure criteria).
- DRIP STOP option for diesel and biodiesel.
- Special type 'H', only for High Flow Dispensers:
Flow rate up to 80 l/min.



Meets EN 13012 : 2001
TÜV approval: P-TÜ7-01930
ATEX approval: SIRA 03ATEX9 487 U



ZVA SLIMLINE 2 + ZVA SLIMLINE 2 GR.

ZVA SLIMLINE 2 GR

- New vapour recovery nozzle for gasoline, also with ethanol content.
- Replaces the ZVA 200 GR from autumn 2008.
- Working pressure 0,5 up to 3,5 bar.
Flow rate up to 45 l/min.
- Fully integrated vapour control valves GRV (On/Off) or GRVP (proportional valve On/Off) at your choice.



for active
vapour recovery
Stage II



GR + GRV

GRVP

Meets EN 13012 : 2001
TÜV approval: P-TÜ7-01930
ATEX approval: SIRA 03ATEX9 487 U
Stage II approvals TÜV Süd No. 85 2 ...

INNER VALUES

-



STAINLESS STEEL TIPPED SPOUT

Enduring protection against wear and tear: even after long service life the fuel flows calm and linear. No spraying, no early shut-off.




INTEGRATED DIESEL DRIP CATCHER AS STANDARD

More cleanliness: Diesel is running down the spout and collected in the Drip Catcher when the nozzle is in the boot. Nozzle cover and comfigrip stay clean and tidy.



ECONOMIC COLOUR CODING

The easy to fit coloured Product Sleeve (EK 043) enables clear fuel grade identification or branding of the nozzle with company colours. Also available as Splashguard (EK 652).



Patents pending for new several constructions details.
Design protection for Europe/China.



DRIP STOP

CLEAN FOR DIESEL

The optional DRIP STOP spout for ZVA Slimline 2 stops dripping diesel and biodiesel within seconds. The dispenser area stays cleaner. Advantage - satisfied customers and a clean environment. Retrofitting possible.



IMPROVED DRAIN-OFF

Due to forward located components and an improved construction, the nozzle drains off fast. This speeds up refuelling and further helps for a clean environment.



CLEARLY LESS EFFORT

Better refuelling comfort, either with or without hold-open latch. The force to pull the lever has been reduced by more than 30 percent. This is appreciated in countries where a hold-open device is not allowed.

FEEL THE DIFFERENCE



ACTIVE PRESSURE CONTROLLED SAFETY SHUT-OFF (DSA)

Optional, for additional safety at prepay dispensers and unmanned petrol stations. The DSA shuts off the nozzle after each refuelling operation.



SENSITIVE CONTROL

Topping-off and to the penny dispensing made easy.

The new intelligent valve poppet opens without effort, so it is still possible to round up - even with high petrol prices.



ZVA SLIMLINE 2 GR: INTEGRATED VAPOUR VALVES

Not only the 'On/Off' vapour valve **GRV**, but also the proportional valve **GRVP** are fully integrated and do not add to the nozzle length. Dry testing with the GRVP has been made even simpler.



SELF EXPLANATORY HOLD OPEN SYSTEM

New easy to use hold-open latch. Simple disassembly after pulling out the latch pin.



COMFORTABLE LEVER

The composite contoured lever provides a comfortable experience for your hand - especially at low temperatures.



IMPROVED SHUT-OFF

The new 'intelligent valve poppet' minimizes pressure peaks and protects the dispensing system. The poppet also provides for an improved shut-off even under demanding operation conditions, such as vapourising or foaming fuels.

ETT

ELAFLEX TANKSTELLENTÉCHNIK GmbH & Co.

Schnackenburgallee 121
22525 Hamburg / Germany

Tel. +49 (040) 540 00 50
Fax +49 (040) 540 00 567
E-Mail info@elaflex.de
Internet www.elaflex.de



GASOLINE without vapour recovery



ACTIVE VAPOUR RECOVERY



DIESEL/BIODIESEL



BIO-FUELS Mixtures i.e. with Ethanol

ELAFLEX 